

LSA-73-L

Linear Straight Actuator
For Offset Single
Locating Pins

*Compact / Light Weight
End of Arm Tools
Dense Tooling*

Rigid and Precise

The LSA-73 uses a ceramic bearing system that provides absolute rigidity with a patented slider for anti-rotation. This technology combined with CNC precision results in RapStop™; a system integral to every unit. RapStop™ replaces external stops and rap couplings while it maintains Z-Axis accuracy to ± 0.050 mm. Tested with over 3,000,000 cycles and a 24kg load, the LSA-73 demonstrated less deflection than any commercially available locating pin and complies with every auto maker's requirements.

Easy to Apply

The LSA-73 is symmetrical and has an extremely narrow profile to fit anywhere and stay out of the way of weld guns and other tooling. The light weight of the unit allows it to be used in end-of-arm-tooling. World standard sensors are employed to simplify controls integration. A Bronze anti-weld slag wiper in a non-conductive mount requires no insulation option. The LSA-73 uses 100% NAMMS standard mounting patterns and pins to assure easy design and assembly on the line. No orifices or other restrictions should be used in the application of Zaytran LSAs.

Weld Immune

The LSA-73 uses the double bronze wiper that has protected tens of thousands of LSA units in automotive factories all over the globe. This system aggressively removes any weld slag from the heat treated shaft.

Maintenance Free

The LSA-73 is guaranteed for the life of the tool (with design sign-off). There are no seals or plastic scrapers to change, no covers with pinch points, and, like all LSAs, the unit is lubricated for life!

ZAYTRAN
AUTOMATION
www.auto-pin.com

Distributed by: **FESTO**
1-800-993-3786
www.festo.com

ZAYTRAN LSA-73-L

Stroke: 25mm or 50mm
 Equivalent Bore Dia.: 57mm
 Max. Pressure: 8.2 bar (120 psi)
 Actuation: Pneumatic
 Extend Force @ 4.1 bar (60 psi): 86.2kg (240 lbs.)
 Retract Force @ 4.1 bar (60 psi): 72.6kg (193 lbs.)
 Assembly Weight: 2.27kg (5.00 lbs.)

The use of orifices or restrictors is not recommended.

Model Nomenclature:

LSA-73-L-XX-YY-ZZ

XX Ports: N (NPT) or G (G-Class)

YY Stroke: 25 (25mm) or 50 (50mm)

ZZ Sensing: SEN (With Sensing), SEN-TRK (Turck Sensing) or NS (No Sensing)

Example: LSA-73-L-N-50-SEN

LSA-73-L with NPT Ports, 50mm of Stroke and Sensing

Sensor Information		
Pin	Color	Function
1	Brown	L+
2	White	Extend
3	Blue	L-
4	Black	Retract

Connector: M12, 4pin, male
 Operating Voltage: 10V to 30V
 Protection Degree: IP65
 For use in direct and alternating field welding systems.

